



R. & P. MATTHEWS PTY.LTD
 TRADING AS MATTHEWS
 PETROLEUM P.O. Box 888,
 Warrnambool. 3280 A.C.N 054 660
 374 A.B.N. 42 054 660 374

Chain & Bar Oil

100, 130, 150, 220 & 320

Product Description

Chain & Bar Oil is a good quality chain and bar lubricant intended to provide cost effective lubrication of chains, sprockets and guide bars of chain saws with either automatic or hand oilers.

Chain & Bar Oil is recommended for the lubrication of the chain bar and sprockets of all types of chainsaws, using either hand – operated or automatic oilers for light to medium use applications.

Chain & Bar Oil comes in different viscosities and thicknesses making it suitable in all environments and applications. In severe conditions and applications, the thicker Chain & Bar Oil 220 & 320 would be recommended.

Applications

Reduces wear:

Reduces wear on the chain bar and sprocket.

Less waste:

The tacky quality of the product reduces sling-off from the chain.

Penetration:

Good penetration into chain links and excellent bar lubrication

Packaging

Bulk, 205 litre drum, 20 litre pail, 5 litre pack

Typical Physical Characteristics

Property	Typical Value				
Grade	100	130	150	220	320
Appearance	Clear, Bright & Tacky				
Density, kg/L	0.873	0.875	0.877	0.880	0.892
Colour	3.0	3.0	3.5	3.5	4.0
Kinematic Viscosity at 40c, cSt	100	130	150	220	320

NOTE: Values stated herein are typical and do not represent a specification.