



R. & P. MATTHEWS PTY.LTD  
 TRADING AS MATTHEWS  
 PETROLEUM P.O. Box 888,  
 Warrnambool. 3280 A.C.N 054 660  
 374 A.B.N. 42 054 660 374

## Gear Oil GL-5 75W90, 80W90 & 85W140

### Product Description

GEAR OIL 75W90, 80W90 & 85W140 are a heavy duty automotive multi-purpose, sophisticated extreme pressure gear lubricant designed to meet the requirements of the API Service Classification GL-5 and Military Specification MIL-L-2105D. It is fully inhibited against foaming, oxidation and corrosion, and contains sulphur/phosphorous extreme pressure additives which ensure that the oil meets all the requirements of modern automotive differentials, manual transmissions and final drives to operate at high load-carrying capacity at sustained high speed under high torque loading conditions, where such gear oils are required.

### Applications

GEAR OIL 75W90, 80W90 & 85W140 should be used in differentials using hypoid and spiral bevel gears as well as manual transmissions which specify this grade of gear oil (is recommended for 4WD gearboxes and transfer drives.)

### Specifications

GEAR OIL 75W/90 & 80W/90 meets or exceeds the following specifications:

- API - GL5
- BTR (BORG WARNER) 5M - 36
- DAIMLER – BENZ 235/2F
- FORD M2C-108A, M2C-105A,
- GENERAL MOTORS HN-1181, HN-1187, HN -1386.
- MACK GO - J
- MILITARY SPECIFICATIONS MIL - L - 2105D
- ROCKWELL STANDARD 0-76-D

GEAR OIL 85W/140 meets or exceeds the following specifications:

- API - GL5
- CLARK MS-8
- FORD SM-2C-1013A
- INTERNATIONAL HARVESTER B-22
- MACK GO-J
- MILITARY SPECIFICATIONS MIL - L - 2105D
- ROCKWELL STANDARD 0-76-A
- WHITE MS-0016

## Typical Physical Characteristics

Property	Typical Value		
SAE Grade	75W90	80W90	85W140
Density, kg/L	0.886	0.888	0.894
Colour	4.0	4.0	4.0
Kinematic Viscosity at 40°C, cSt	140	143	333
Kinematic Viscosity at 100°C, cSt	14.8	16.6	32.2
Viscosity Index	116	124	134
Phosphorous, %wt	0.090	0.083	0.083
SAE Grade	75W90	80W90	85W140
Density, kg/L	0.886	0.888	0.894
Colour	4.0	4.0	4.0

**NOTE:** Values stated herein are typical and do not represent a specification.