



R. & P. MATTHEWS PTY.LTD
 TRADING AS MATTHEWS
 PETROLEUM P.O. Box 888,
 Warrnambool. 3280 A.C.N 054 660
 374 A.B.N. 42 054 660 374

Hydraulic Oil ISO68

ISO 68

Product Description

HYDRAULIC OIL ISO68 is a general purpose anti-wear hydraulic oil.

Operating Temperature Range

HYDRAULIC OIL ISO68 are an excellent economic choice for use in hydraulic systems calling for a zinc-based anti-wear oils.

HYDRAULIC OIL ISO68 contains rust, oxidation and foam inhibitors as well as zinc based anti-wear additives.

HYDRAULIC OIL ISO68 is compatible with other hydraulic oils that contain a zinc based anti-wear system.

Specifications

HYDRAULIC OIL ISO68 meets or exceeds the requirements of:

- Denison HF-0, HF-02
- Wet phase (II) of the Denison T6C-020 vane pump
- DIN 51 51524 Parts 2 and 3 (HLP & HVLP)
- Eaton Vickers M-2950-S (35VQ25)
- Eaton Vickers I-286-S
- Cincinnati Machine P-68, P-69 and P-70
- AFNOR NF E 48-603 (HM, HV)
- AFNOR NF E 48-609, NF E 48-691 Filterability

Packaging

205 litre drum, 20 litre Cube, 5 litre pack

Typical Physical Characteristics

Property	Typical Value
ISO Viscosity Grade	68
Density, kg/L	0.878
Colour	2.0
Kinematic Viscosity at 40c, cSt	68

NOTE: Values stated herein are typical and do not represent a specification.